



LIQUID WAX CLEANER


Clean and refresh in one step!



3029
Clear



3087 White
Transparent



PRODUCT DESCRIPTION

Clear or transparent wax-based care product for occasionally refreshing interior wooden flooring with Polyx®-Oil surfaces, furniture as well as other interior oiled and waxed wood surfaces.

Through appropriate care, the surface is provided with the natural, safe hard waxes (carnauba and candelilla waxes). The floor stays hard-wearing without forming a film.

RECOMMENDED USE

Osmo Liquid Wax Cleaner / Spray is ideal for removing tough stains, e.g. grease or shoe polish, and best suited for refreshing all surfaces treated with Osmo Polyx®-Oil.

INGREDIENTS

Based on natural plant waxes (carnauba wax, candelilla wax); paraffin, aliphatic hydrocarbons (>30%). Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.77-0.8 g/cm³
Viscosity: >30s DIN EN ISO 2431/3 mm, viscid
Odour: faint/mild, odourless after drying
Flash point: >60°C acc. DIN EN ISO 2719

Storage

Up to 5 years and longer if container is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

SURFACE PREPARATION

Wood surface must be dust-free and dry. For this purpose generally a dust mop, a mop or a vacuum cleaner is suitable. For simple cleaning and maintenance, Osmo Opti-Set (Dust-Mop, Micro-Mop Plush and an Active Fibre Cloth) is highly recommended.

For cleaning high-traffic and heavily soiled flooring, e.g. in public spaces, use Osmo Micro-Mop (water mixed with Osmo Wash and Care) and buffed dry afterwards.

METHODS OF APPLICATION

Manual application:

For removing stains and for intensive maintenance, please use Osmo Liquid Wax Cleaner with our Active Fibre Cloth (approx. 2 teaspoons per m²).

Rub away especially tough stains with Osmo Liquid Wax Cleaner with a cloth or a Scotchpad.

Mechanically application:

Apply Osmo Liquid Wax Cleaner with a single disc machine and a white pad (approx. 2 teaspoons per m²). Spread Liquid Wax Cleaner on the surface evenly and massage in.

Should streaks appear, either turn the pad over or use a new pad, also see FloorXCenter description.

To achieve a higher gloss level, polish the dried surface with a white pad.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME

Approx. 30-40 minutes (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

COVERAGE

Product coverage of Osmo Liquid Wax Cleaner / Spray strongly depends on the absorption and on the amount of dirt and stains on the substrate. (1 litre of care product covers approx. 80-100 m², 2 teaspoons for approx. 1 m²).



NOTE

By applying hard waxes (carnauba and candelilla waxes) regularly, the floor is refreshed, and resistance to cracks and wear is improved.

However, it is absolutely necessary to return the required oil components of Polyx®-Oil to the floor within the course of one year.

Only apply thinly; otherwise footprints may appear.

Please use only Osmo Liquid Wax Cleaner White on white subsurfaces.

On especially high traffic areas, re-apply Osmo Polyx®-Oil to the cleaned area.

CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Safety data sheet available on request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

3029 Clear

3087 White Transparent

SIZES

Liquid Wax Cleaner: 0.5 L; 1 L; 10 L

Liquid Wax Cleaner White: 1 L; 10 L

Liquid Wax Cleaner Spray Clear: 400 ml spray (not white transparent)

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/15