

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Liquid Wax Cleaner Spray, clear

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture No further relevant information available.

Maintenance product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Further information obtainable from:

Product safety department
Phone: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture**Classification according to Regulation (EC) No 1272/2008**

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Warning! Pressurized container.

Classification system: The classification is according to the latest editions of the EU-lists and extended by company and literature data.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008****Hazard pictograms**

The product is classified and labelled according to the CLP regulation.



GHS02

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 1)





Signal word	Danger
Hazard statements	H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.
Precautionary statements	<p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P103 Read label before use.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P262 Do not get in eyes, on skin, or on clothing.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.</p> <p>P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
Additional information:	<p>EUH066 Repeated exposure may cause skin dryness or cracking.</p> <p>Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.</p> <p>Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.</p>
2.3 Other hazards	
Results of PBT and vPvB assessment	
PBT:	Not applicable.
vPvB:	Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-49-0 EC number: 927-241-2 Index number: 649-328-00-1 Reg.nr.: 01-2119471843-32	aliphatic hydrocarbons, C9-C10  Xn R65 R10-52/53-66-67 <hr style="border-top: 1px dashed black;"/>  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H336 Aquatic Chronic 3, H412	50-75%
--	--	--------

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31










Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 2)

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane  F+ R12  Flam. Gas 1, H220  Press. Gas, H280	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane  F+ R12  Flam. Gas 1, H220  Press. Gas, H280	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8	isobutane  F+ R12  Flam. Gas 1, H220  Press. Gas, H280	≤ 2.5%

Regulation (EC) No 648/2004 on detergents / Labelling for contentsaliphatic hydrocarbons ≥ 30%**Additional information:** For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

In case of unconsciousness place patient stably in side position for transportation.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:**

Water with full jet

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 3)

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
Ensure adequate ventilation.

6.4 Reference to other sections

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.
Keep receptacles tightly sealed.
Use only in well ventilated areas.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 4)

Further information about storage conditions:

Store only outside or in explosion proof rooms.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-49-0 aliphatic hydrocarbons, C9-C10

TWA (8 H)	Short-term value: 1000 mg/m ³ Source UK SIA
-----------	---

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

74-98-6 propane

AGW	Long-term value: 1800 mg/m ³ , 1000 ppm 4(II);DFG
-----	---

75-28-5 isobutane

OEL	Short-term value: 3800 mg/m ³ , 750 ppm Long-term value: 1900 mg/m ³ , 600 ppm EH 40/97
-----	---

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.
Immediately remove all soiled and contaminated clothing
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.

Respiratory protection:

Not necessary if room is well-ventilated.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 5)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter P3

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Aerosol

Colour: Colourless

Odour: Characteristic

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

Flash point: Not applicable, as aerosol.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.8 Vol %

Upper: 8.5 Vol %

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 6)

Vapour pressure at 20 °C:	10 hPa
Density:	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

10.3 Possibility of hazardous reactions

Forms explosive gas mixture with air.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)
106-97-8 butane		
Inhalative	LC50 / 4h	658 mg/l (rat)

Primary irritant effect:

on the skin:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

Irritating effect.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

Sensitization: No sensitizing effects known.

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

64742-48-9 aliphatic hydrocarbons, C10-C13

Biolog. Abbaubarkeit	(-) (leicht abbaubar)
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
16 05 05	gases in pressure containers other than those mentioned in 16 05 04
15 01 11	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 8)

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR
Class 2 5F Gases.
Label 2.1

IMDG, IATA

Class 2.1
Label 2.1

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Gases.
Danger code (Kemler): -
EMS Number: F-D,S-U

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

ADR
Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D

UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.01.2014

Version number 11

Revision: 27.01.2014

Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
 H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
 R10 Flammable.
 R12 Extremely flammable.
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R65 Harmful: may cause lung damage if swallowed.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

*** Data compared to the previous version altered.**